

MF65™

Tri-Laminate Cryogenic Vapour Barrier Tape

Product Description

MF65™ is a premium vapour barrier tape product. Manufactured as a three-layer lamination of polyester film(12 micron), aluminium foil(25 micron) and polyester film(12 micron), and coated with a cold weather pressure sensitive acrylic adhesive, this premium grade tape product is specifically designed as a vapour barrier in thermal insulations.

This conformable tri-laminate tape applies the outstanding chemical characteristics of its polyester and aluminium construction to provide outstanding performance; exceling in extreme cold or humid conditions. Suitable for both internal or external applications and providing a complete vapour stop solution, MF65 meets the demanding requirements of the today's professional installers.

Product Data

Item	Value	Standard
Adhesive	Solvent Acrylic	
Product Thickness	49 micron	DIN 53 3570
Material Weight	108 g/m ²	EN 2286
Adhesive Thickness	50 micron	
Elongation	63%	EN 527-3
Tensile Strength	109 N/15mm	EN 527-3
Peel Strength	7.9 N/cm	PSTC-101
Water Vapour Permeability	<0.01 g/m ² 24hr	ISO 15105-2
Application Temperature	-30°C to 130°C	

Markets

- Asbestos abatement
- Construction
- HVAC
- Process plant
- Marine & offshore

Product Characteristics

- Bright metallic finish
- High quality siliconised release liner
- Available in 48, 72, 98 & 1200mm widths

Features

- Laminated aluminium backing providing excellent reflection of both heat and light sources.
- Extremely high-quality solvent acrylic high tack adhesive offering reliable and durable sealing and bonding characteristics at extreme cold and high humidity environments.
- Excellent aging resistance for both internal and external applications.

Typical Applications

Widely used in the HVAC industry as a vapour barrier for the jointing and sealing of insulation materials, fibreglass blankets, duct board, pipe sections and seams. Suited for exterior use applications and for use cases in extreme cold and high humidity environments.



Technical Data Sheet

Also used in other industrial applications requiring an adhesive tape with similar characteristics and benefits. Please check with a technical product expert to determine suitability for a particular purpose prior to use.

Storage / Shelf Life

12 months when stored in original, unopened packaging at 21°C (70°F) / 50% relative humidity, and kept out of direct sunlight.

Directions For Use:

Surface Preparation

Ensure all surfaces are dry and clean, free from dirt, dust, grease, oil, silicones or other contaminants.

Ensure firm pressure is applied to the tape to provide the best adhesive bond, and that sufficient tape is applied (of at least 25mm) either side of joints to provide a long-lasting seal.

Application

Remove the release paper from the section of MF65™ tape, taking care not to touch the adhesive surface.

Align the tape centrally over the joint. Pull the tape taut and then press down firmly over the entire joint area.

Rub the tape to remove any wrinkles or folds.

Legal Notices

The information, and, in particular, the recommendations relating to the application and end-use of ProTech Global Ltd products, are given in good faith based on ProTech Global Ltd.'s current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with ProTech Global Ltd.'s recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. ProTech Global Ltd reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

About ProTech Global Ltd

ProTech Global Ltd is a UK based company that has manufactured anti-corrosion products for over 25 years. With many years' experience in differing types of protection scenarios, ProTech Global Ltd has a reputation as a trusted supplier and partners with many corporations worldwide.

ProTech Global Ltd:

Unit 3 Lynx Crescent, Weston Industrial Estate, Weston-super-Mare, BS24 9DJ, UK

Tel: +44 (0)117 298 0573

Email: sales@protechglobal.co.uk