













TAPE COMPARISON CHART



Industrial adhesive tapes for asbestos abatement, HVAC, construction, process plant, marine & offshore markets

● Excellent ◐ Good ○ Not applicable

| TAPE CHARACTERISTICS | GT30HT | GT30R | GT40HT | GT50HT | GTB65 | GTR55 | GT1585HT | GT1625HT | GT1629HT | GT8025HT | MB30 | MF65 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Suitable for the sealing of foil faced insulation | ● | ● | ● | ● | ○ | ● | ○ | ◐ | ◐ | ○ | ○ | ◐ |
| Suitable for application in cold temperatures | ● | ○ | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Suitable for hot and humid environments | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Suitable for cryogenic applications | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ● |
| Suitable to match internal matt black facings | ○ | ○ | ○ | ○ | ● | ○ | ○ | ○ | ○ | ○ | ● | ○ |
| Suitable to seal joints to FSK faced Insulation | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ● | ● | ○ | ○ | ○ |
| Suitable to seal joints to ASJ faced Insulation | ○ | ○ | ○ | ○ | ● | ● | ○ | ○ | ○ | ● | ○ | ● |
| Moisture resistant | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| High peel adhesive strength | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| High sheer adhesive strength | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Cold weather acrylic adhesive | ● | ○ | ● | ● | ○ | ● | ● | ● | ● | ● | ○ | ● |
| Rubber based adhesive | ○ | ● | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ● | ○ |
| No added chlorines or chlorides in adhesive | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Suitable for stress fracture pipe wrap protection | ○ | ○ | ○ | ● | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Suitable for the sealing of housewrap materials | ○ | ○ | ○ | ○ | ○ | ○ | ● | ○ | ○ | ○ | ○ | ○ |
| KEY PRODUCT DATA | | | | | | | | | | | | |
| Thickness (facing) | 30 micron | 30 micron | 40 micron | 50 micron | 30 micron | 43 micron | 38 micron | 120 micron | 120 micron | 125 micron | 30 micron | 49 micron |
| Tensile strength | 45N/25mm | 25N/25mm | 55N/10mm | 45N/25mm | 1.2N/10mm | 100N/25mm | 15N/25mm | 120N/25mm | 120N/25mm | 215N/25mm | 20N/10mm | 109N/15mm |
| Elongation | 3% | 3% | 3% | 3% | 3-5% | 3% | 100% | 1% | 1% | 1% | 5% | 63% |
| Application temperature (°C) | -20 to +40 | +10 to +40 | -20 to +40 | -20 to +40 | -10 to +75 | +10 to +40 | +10 to +40 | +10 to +40 | +10 to +40 | +10 to +40 | +10 to +75 | -30 to +130 |
| Temperature range (°C) | -35 to +120 | -20 to +80 | -35 to +120 | -35 to +120 | -20 to +75 | -30 to +120 | -30 to +100 | -30 to +80 | -30 to +120 | -30 to +80 | -40 to +80 | -30 to +130 |
| Available colours | silver | silver | silver | silver | black | silver | red, green, blue, black & white | silver | silver | white | black | silver |
| Available widths (mm) | 48,72 & 96 | 48,72 & 96 | 48,72 & 96 | 48,72 & 96 | 50,75, 100 & 1200 | 48,72 & 96 | 48,63 & 72 | 48,72 & 96 | 48,72 & 96 | 48,72 & 96 | 50,75,100 & 1200 | 48,72,96 & 1200 |
| FIRE RATING | | | | | | | | | | | | |
| BS 476 / Class 0 | ● | ● | ● | ● | ○ | ● | ○ | ● | ○ | ○ | ○ | ○ |
| ASTM E84 / UL 723 | ○ | ○ | ○ | ● | ○ | ○ | ○ | ● | ○ | ○ | ○ | ○ |
| QR code |  |  |  |  |  |  |  |  |  |  |  |  |